





# ФИТИНГИ СТАНДАРТА DKOL(S)

Фитинг DKOL (штуцер) (наружная метрическая резьба, внутренний конус 24°)




Внутренний диаметр рукава		Размер резьбы		Размеры (мм)				
DN	Size	Дюйм	F	Труба	H	L	E	S
6	6,4	1/4"	M12x1,5	6	23,0	52	6	14
6	6,4	1/4"	M14x1,5	8	23,0	52	8	14
6	6,4	1/4"	M16x1,5	10	24,0	53	10	17
6	6,4	1/4"	M18x1,5	12	25,0	54	12	19
8	8,0	5/16"	M16x1,5	0	24,0	53	10	17
8	8,0	5/16"	M18x1,5	12	25,0	54	12	19
10	9,5	3/8"	M18x1,5	10	24,0	55	10	17
10	9,5	3/8"	M18x1,5	12	25,0	56	12	19
10	9,5	3/8"	M22x1,5	15	27,0	58	15	24
12	12,7	1/2"	M22x1,5	15	29,0	62	15	24
12	12,7	1/2"	M28x1,5	18	29,0	62	18	27
16	16,0	5/8"	M28x1,5	18	29,0	65	18	27
19	19,0	3/4"	M28x1,5	18	30,0	71	18	27
19	19,0	3/4"	M30x2	22	32,0	73	22	32
25	25,4	1"	M36x2	28	33,0	88	28	36
32	31,8	1.1/4"	M45x2	35	38,0	99	35	46
38	38,1	1.1/2"	M52x2	42	41,0	111	42	55




Фитинг DKOL (гайка) (внутренняя метрическая резьба, наружный конус 24° с резиновым кольцом (O-Ring))

Внутренний диаметр рукава		Размер резьбы		Размеры (мм)				
DN	Size	Дюйм	F	Труба	H	L	E	S
6	6,4	1/4"	M12x1,5	6	23,0	52	17	
6	6,4	1/4"	M14x1,5	8	24,0	53	17	
6	6,4	1/4"	M16x1,5	10	25,0	54	19	
6	6,4	1/4"	M18x1,5	12	25,0	54	22	
8	8,0	5/16"	M16x1,5	10	25,0	54	19	
8	8,0	5/16"	M18x1,5	12	25,0	54	22	
10	9,5	3/8"	M18x1,5	10	26,0	56	19	
10	9,5	3/8"	M18x1,5	12	25,0	56	22	
10	9,5	3/8"	M22x1,5	15	27,0	57	27	
12	12,7	1/2"	M22x1,5	15	27,0	60	27	
16	16,0	5/8"	M28x1,5	18	28,0	64	32	
16	16,0	5/8"	M27x1,5	18	28,0	64	32	
19	19,0	3/4"	M30x2	22	31,0	72	36	
25	25,4	1"	M36x2	28	33,0	88	41	
32	31,8	1.1/4"	M45x2	35	37,0	98	50	
38	38,1	1.1/2"	M52x2	42	39,0	109	60	




Фитинг 90° DKOL (гайка) (внутренняя метрическая резьба, наружный конус 24° с резиновым кольцом (O-Ring))

Внутренний диаметр рукава		Размер резьбы		Размеры (мм)					
DN	Size	Дюйм	F	Труба	H	L	K	S	
6	6,4	1/4"	M12x1,5	6	24,0	52	28	17	
6	6,4	1/4"	M14x1,5	8	24,0	52	28	17	
6	6,4	1/4"	M16x1,5	10	24,0	52	30	19	
6	6,4	1/4"	M18x1,5	12	24,0	52	31	22	
8	8,0	5/16"	M16x1,5	10	31,0	59	33	19	
8	8,0	5/16"	M18x1,5	12	31,0	59	34	22	
10	9,5	3/8"	M18x1,5	10	34,0	64	36	19	
10	9,5	3/8"	M18x1,5	12	34,0	64	35	22	
10	9,5	3/8"	M22x1,5	15	34,0	64	38	27	
12	12,7	1/2"	M22x1,5	15	41,0	74	41	27	
16	16,0	5/8"	M28x1,5	18	49,0	85	49	32	
16	16,0	5/8"	M27x1,5	18	49,0	85	49	32	
19	19,0	3/4"	M30x2	22	58,0	99	54	36	
25	25,4	1"	M36x2	28	74,0	129	88	41	
32	31,8	1.1/4"	M45x2	35	92,0	153	88	50	
38	38,1	1.1/2"	M52x2	42	108,0	179	96	60	




Фитинг 45° DKOL (гайка) (внутренняя метрическая резьба, наружный конус 24° с резиновым кольцом (O-Ring))

Внутренний диаметр рукава		Размер резьбы		Размеры (мм)					
DN	Size	Дюйм	F	Труба	H	L	K	S	
6	6,4	1/4"	M12x1,5	6	43	71,5	19	17	
6	6,4	1/4"	M14x1,5	8	39,5	66	16	17	
6	6,4	1/4"	M16x1,5	10	40,5	69	16,5	19	
6	6,4	1/4"	M18x1,5	12	42,0	70,5	18	22	
8	8,0	5/16"	M16x1,5	10	48,0	76,5	18	19	
8	8,0	5/16"	M18x1,5	12	49,0	77,5	19	22	
10	9,5	3/8"	M18x1,5	10	58,0	88	23,5	19	
10	9,5	3/8"	M18x1,5	12	53,0	83,5	19	22	
10	9,5	3/8"	M22x1,5	15	55,0	85,5	21	27	
12	12,7	1/2"	M22x1,5	15	62,0	95	22,5	27	
16	16,0	5/8"	M28x1,5	18	79,0	115	26	32	
16	16,0	5/8"	M27x1,5	18	79,0	115	26	32	
19	19,0	3/4"	M30x2	22	87,0	127,5	31,0	36	
25	25,4	1"	M36x2	28	109,0	164,0	40,0	41	
32	31,8	1.1/4"	M45x2	35	137,5	198,5	53,0	50	
38	38,1	1.1/2"	M52x2	42	161,5	231,5	56,5	60	



Фитинг DKOS (штуцер) (наружная метрическая резьба, внутренний конус 24°)

Внутренний диаметр рукава		Размер резьбы		Размеры (мм)				
DN	Size	Дюйм	F	Труба	H	L	E	S
6	6,4	1/4"	M16x1,5	6	25,0	54	8	17
6	6,4	1/4"	M18x1,5	10	26,0	55	10	19
8	8,0	5/16"	M18x1,5	10	26,0	55	10	19
10	9,5	3/8"	M18x1,5	10	26,0	57	10	19
10	9,5	3/8"	M20x1,5	12	27,0	58	12	22
10	9,5	3/8"	M22x1,5	14	29,0	60	14	24
12	12,7	1/2"	M22x1,5	14	30,0	63	14	24
12	12,7	1/2"	M24x1,5	16	31,0	64	16	27
16	16,0	5/8"	M30x2	20	33,0	69	20	32
19	19,0	3/4"	M30x2	20	34,0	70	20	32
19	19,0	3/4"	M36x2	25	36,0	77	25	36
25	25,4	1"	M36x2	25	37,0	82	25	36
25	25,4	1"	M42x2	30	41,0	96	30	46
32	31,8	1.1/4"	M42x2	30	42,0	103	30	46
32	31,8	1.1/4"	M52x2	38	46,0	107	38	55
38	38,1	1.1/2"	M52x2	38	47,0	117	38	55



Фитинг DKOS (гайка) (внутренняя метрическая резьба, наружный конус 24° с резиновым кольцом (O-Ring))

Внутренний диаметр рукава		Размер резьбы		Размеры (мм)				
DN	Size	Дюйм	F	Труба	H	L	E	S
6	6,4	1/4"	M16x1,5	8	24,0	53	19	
6	6,4	1/4"	M18x1,5	10	25,0	54	22	
8	8,0	5/16"	M18x1,5	10	25,0	54,0	22	
8	8,0	5/16"	M20x1,5	12	25,0	54,0	24	
10	9,5	3/8"	M18x1,5	10	25,0	56,0	22	
10	9,5	3/8"	M20x1,5	12	25,0	56,0	24	
10	9,5	3/8"	M22x1,5	14	29,0	60,0	27	

