


ФИТИНГИ СТАНДАРТА NPTF

Фитинг NPTF (наружная двойная коническая резьба, внутренний конус 60°)



DN	Внутренний диаметр рукава		Размер резьбы		Размеры (мм)		
	Size	Дюймы	F	N	L	S	
6	6,4	1/4"	1/4"-18	26,5	55,0	15	
6	6,4	1/4"	3/8"-18	27,5	56,0	19	
8	8,0	5/16"	1/4"-18	26,5	55,0	15	
8	8,0	5/16"	3/8"-18	27,5	56,0	19	
10	9,5	3/8"	1/4"-18	26,5	57,0	15	
10	9,5	3/8"	3/8"-18	27,5	58,0	19	
10	9,5	3/8"	1/2"-14	33,5	64,0	22	
12	12,7	1/2"	3/8"-18	28,5	61,5	19	
12	12,7	1/2"	1/2"-14	34,5	67,5	22	
16	16,0	5/8"	1/2"-14	34,5	70,5	22	
16	16,0	5/8"	3/4"-14	36,2	72,2	27	
19	19,0	3/4"	3/4"-14	37,2	76,2	27	
19	19,0	3/4"	1"-11,5	42,5	83,5	36	
25	25,4	1"	1"-11,5	43,5	86,5	36	
25	25,4	1"	1 1/4"-11,5	45,6	100,6	46	
32	31,8	1 1/4"	1 1/4"-11,5	46,1	107,1	46	
38	38,1	1 1/2"	1 1/2"-11,5	50,1	120,4	50	
51	50,8	2"	2"-11,5	54,2	130,2	65	