



# ФИТИНГИ СТАНДАРТА ORFS




Фитинг ORFS (шпунер) (двойная резьба)

DN	Внутренний диаметр рукава		Размер резьбы	Размеры (мм)		
	мм	Дюйм		F	H	L
6	6,4	1/4"	9/16-18	23,5	52	17
8	8,0	5/16"	11/16-16	26,0	54,5	19
10	9,5	3/8"	11/16-16	26,0	56,5	19
10	9,5	3/8"	13/16-16	28,0	58,5	22
12	12,7	1/2"	13/16-16	29,0	62	22
16	16,0	5/8"	1-14	33,5	69,5	27
19	19,0	3/4"	1 3/16-12	36,0	77	32
25	25,4	1"	1 7/16-12	38,0	93	41
32	31,8	1 1/4"	1 11/16-12	40,0	101	46
40	38,1	1 1/2"	2"-12	43,0	113,5	55




Фитинг ORFS (гайка) (двойная резьба)

DN	Внутренний диаметр рукава		Размер резьбы	Размеры (мм)		
	мм	Дюйм		F	H	L
6	6,4	1/4"	9/16-18	21,0	48,5	17
8	8,0	5/16"	11/16-16	23,0	51,5	22
10	9,5	3/8"	11/16-16	23,0	53,5	22
10	9,5	3/8"	13/16-16	26,0	56,5	24
12	12,7	1/2"	13/16-16	26,5	59,5	24
16	16,0	5/8"	1-14	30,0	66	30
19	19,0	3/4"	1 3/16-12	33,5	74,5	36
25	25,4	1"	1 7/16-12	35,5	90,5	41
32	31,8	1 1/4"	1 11/16-12	36,0	97	50
40	38,1	1 1/2"	2"-12	36,5	107	60



Фитинг 90° ORFS (гайка) (двойная резьба)

DN	Внутренний диаметр рукава		Размер резьбы	Размеры (мм)			
	мм	Дюйм		F	H	L	K
6	6,4	1/4"	9/16-18	24,0	52	21	17
6	6,4	1/4"	11/16-16	24,0	52	24	22
10	9,5	3/8"	11/16-16	34,0	64	30	22
10	9,5	3/8"	13/16-16	34,0	64	33	24
12	12,7	1/2"	13/16-16	41,0	74	36	24
16	16,0	5/8"	1-14	49,0	85	44	30
19	19,0	3/4"	1 3/16-12	58,0	99	52	36
25	25,4	1"	1 7/16-12	74,0	129	62	41
32	31,8	1 1/4"	1 11/16-12	92,0	153	74	50
38	38,1	1 1/2"	2-12	106,0	179	83	60



Фитинг 45° ORFS (гайка) (двойная резьба)

DN	Внутренний диаметр рукава		Размер резьбы	Размеры (мм)			
	мм	Дюйм		F	H	L	K
6	6,4	1/4"	9/16-18	35,5	64	12	17
6	6,4	1/4"	11/16-16	7,0	85,5	13	22
10	9,5	3/8"	11/16-16	48,5	79	15	22
10	9,5	3/8"	13/16-16	51,0	81,5	17	24
12	12,7	1/2"	13/16-16	56,0	91	19	24
16	16,0	5/8"	1-14	73,5	109,5	21	30
19	19,0	3/4"	1 3/16-12	82,5	123,5	29	36
25	25,4	1"	1 7/16-12	102,5	157,5	35	41
32	31,8	1 1/4"	1 11/16-12	126,5	187,5	43	50
38	38,1	1 1/2"	2-12	140,5	219,5	45	60