



# ФИТИНГИ СТАНДАРТА JIS

Фитинг 90° JIS (гайка) (внутренняя дюймовая резьба, внутренний конус 74°)



Внутренний диаметр рукава		Размер резьбы		Размеры (мм)			
DN	мм	Дюймы	F	H	L	K	S
6	6,4	1/4"	7/16-20	24,0	52	24	15
6	6,4	1/4"	1/2-20	24,0	52	25	17
6	6,4	1/4"	9/16-18	23,5	52	27	19
8	8,0	5/16"	9/16-18	30,5	59	31	19
10	9,5	3/8"	9/16-18	33,5	64	37	19
10	9,5	3/8"	3/4-16	33,5	64	36	24
12	12,7	1/2"	3/4-16	41,0	74	41	24
12	12,7	1/2"	7/8-14	41,0	74	42	27
12	12,7	1/2"	1 1/16-12	41,0	74	46	32
16	16,0	5/8"	7/8-14	49,0	85	47	27
16	16,0	5/8"	1 1/16-12	49,0	85	51	32
19	19,0	3/4"	1 1/16-12	58,0	99	57	32
19	19,0	3/4"	1 5/16-12	58,0	99	65	41
25	25,4	1"	1 1/16-12	74,0	129	76	32
25	25,4	1"	1 5/16-12	74,0	129	72	41
32	31,8	1 1/4"	1 5/8-12	92,0	153	87	50
38	38,1	1 1/2"	1 7/8-12	108,0	179	100	55
51	50,8	2"	2 1/2-12	142,0	216	126	70



Фитинг 45° JIS (гайка) (внутренняя дюймовая резьба, внутренний конус 74°)

Внутренний диаметр рукава		Размер резьбы		Размеры (мм)			
DN	мм	Дюймы	F	H	L	K	S
6	6,4	1/4"	7/16-20	37,0	66	14	15
6	6,4	1/4"	1/2-20	38,0	67	15	17
6	6,4	1/4"	9/16-18	9,5	68	16	19
8	8,0	5/16"	9/16-18	47,5	76	18	19
10	9,5	3/8"	9/16-18	53,5	84	20	19
10	9,5	3/8"	3/4-16	53,5	84	20	24
12	12,7	1/2"	3/4-16	61,5	94,5	22	24
12	12,7	1/2"	7/8-14	62,5	95,5	23	27
12	12,7	1/2"	1 1/16-12	65,0	98	26	32
16	16,0	5/8"	7/8-14	76,0	112	24	27
16	16,0	5/8"	1 1/16-12	78,5	114,5	26	32
19	19,0	3/4"	1 1/16-12	85,5	126,5	32	32
19	19,0	3/4"	1 5/16-12	91,0	132	38	41
25	25,4	1"	1 1/16-12	112,5	167,5	45	32
25	25,4	1"	1 5/16-12	107,5	162,5	40	41
25	25,4	1"	1 5/8-12	111,0	166	43	50
32	31,8	1 1/4"	1 5/8-12	135,5	195,5	52	50
38	38,1	1 1/2"	1 7/8-12	161,0	231	57	55
51	50,8	2"	2 1/2-12	205,5	281	66,5	70